

Technical data sheet


Spectral EXTRA 785
Universal degreaser

Spectral EXTRA 785

RELATED PRODUCTS
Universal degreaser

PROPERTIES

- Universal degreaser
- Efficiently removes fat and silicone
 - Not aggressive, mild smell
 - Gentle smell

USE	
<ul style="list-style-type: none"> • Steel • Aluminium • Galvanised steel • Stainless steel • Old paint coatings • Acrylic primers • Polyester putties 	
CONTENT OF VOLATILE ORGANIC COMPOUNDS	
VOC II/B/a limit	850 g/l
Actual VOC content	780 g/l
PROCEDURE	
	<p>The surface should be washed 2-3 times (in case atomizer max. 2 times).</p> <p>A clean piece of cloth should be used each time.</p> <p>One should wait until the remover evaporates completely before the application of the coat.</p>
STORAGE CONDITIONS	
<p>Store in a dry and cool room, away from sources of fire and heat.</p> <p>Avoid direct exposure to sunlight.</p>	
SHELF LIFE	
Spectral EXTRA 785	24 months/20 °C
SAFETY	
See Safety Data Sheet.	
OTHER INFORMATIONS	
<p>The effectiveness of our systems results from laboratory research and many years of experience. The data contained herein meets the current knowledge about our products and their application potential. We ensure high quality, provided the user follows the instructions and the work is performed in accordance with good workmanship. It is necessary to do a test application of the product due to its potentially different reaction with different materials. We may not be held liable for defects if the final result was affected by factors beyond our control.</p>	